

CLAIMS

I claim:

1. An optical interleaver comprising:

a first collimating lens for collimating an input optical signal into collimated beams and a second collimating lens for focusing said collimated parallel beams into an output optical fiber; and

a phase delay difference generating means for generating a phase-delay difference between portions of said collimated parallel beams for generating an interference in said second collimating lens for selectively enhance signal transmission of certain wavelengths.

112  
problem

2 The optical interleaver of claim 1 wherein:

said phase delay difference generating means comprising a glass plate blocking a portion of said collimated parallel beams for generating a phase delay for a portion of said collimated parallel beams passing therethrough.

3 The optical interleaver of claim 1 wherein:

said phase delay difference generating means comprising a glass plate having an upper portion covering an upper portion of said collimated parallel beams and said glass plate having a lower portion covering a lower portion of said collimated parallel beams for generating a phase delay difference between said upper portion and lower portion of said collimated parallel beams.

5

10

15

20

25

30

Sub  
A1

09705166-10100

4 The optical interleaver of claim 1 further comprising:

a control means for controlling said phase delay difference  
generating means for selectively generating signal  
transmission at different wavelengths according to said  
interference generated in said second collimating lens.

5 The optical interleaver of claim 4 further comprising:

said phase delay difference generating means comprising a  
glass plate having a plurality predefined segments with  
different combination of plate-thickness and diffraction  
index wherein said phase delay difference generating means  
is controlled by said control means for selectively generating  
signal transmission at different wavelengths with a  
predefined program.

6 The optical interleaver of claim 1 wherein:

said phase delay difference generating means comprising a  
set of cascaded March-Zanter<sup>inter</sup>-interferometer for generating a  
series of band-pass signal transmissions.

7 The optical interleaver of claim 6 wherein:

each of said a set of cascaded March-Zanter interferometer  
comprising a phase delay plate and a half-pitch GRIN lens.

8 The optical interleaver of claim 6 wherein:

each of said a set of cascaded March-Zanter interferometer  
comprising a phase delay plate and a pair of focus and  
collimating lenses.

Sub  
AI  
inf

09705166-140100

9. The optical interleaver of claim 1 further comprising:

a reflective means for reflecting a portion of said collimated beams as second group of parallel beams transmitted along a second optical path away from said collimated parallel beams;

a third collimating lens for focusing said second group of parallel beams into a second output optical fiber; and

a second phase delay difference generating means for generating a second phase-delay difference between portions of said second group of parallel beams for generating an interference in said third collimating lens for selectively enhance signal transmission of a second set of wavelengths outputting from said second optical fiber.

10 The optical interleaver of claim 9 wherein:

said reflective means comprising a partially reflective front surface of said phase delay means and a mirror for reflecting a portion of said collimated beams as second group of parallel beams transmitted along a second optical path away from said collimated parallel beams.

Sub  
A1  
end

09705165-110400

11 An optical interleaver comprising:

5

a phase difference generating means for generating a phase difference between different portion of optical beams for selectively enhancing signal transmissions at certain wavelengths resulting from interference between said different portions of optical beams.

12 The optical interleaver of claim 11 further comprising:

10

a control means for controlling said phase difference generating means controlling a selection of certain wavelengths for enhanced signal transmission.

13 The optical interleaver of claim 11 wherein:

15

said phase difference generating means further comprising an optical element for transmitting optical beams therethrough.

20

14 The optical interleaver of claim 13 wherein:

25

said phase difference generating means further comprising said optical element for transmitting optical beams therethrough with at least two portions of different thicknesses.

15 The optical interleaver of claim 13 wherein:

30

said phase difference generating means further comprising said optical element for transmitting optical beams therethrough with at least two portions of different diffraction indexes.

35

Sub  
A2

09705466-140400

16

17 A method for configuring an optical interleaver comprising:

employing a phase difference generating means for generating a phase difference between different portion of optical beams for selectively enhancing signal transmissions at certain wavelengths resulting from interference between said different portions of optical beams.

17

18 The method of claim 17 further comprising:

employing a control means for controlling said phase difference generating means controlling a selection of certain wavelengths for enhanced signal transmission.

18

19 The method of claim 17 wherein:

said step of employing said phase difference generating means further comprising a step of employing an optical element for transmitting optical beams therethrough.

19

20 The optical interleaver of claim 19 wherein:

said step of employing said optical element for transmitting said optical beams therethrough is a step of employing said optical element with at least two portions of different thicknesses for transmitting said beams through.

20

21 The optical interleaver of claim 19 wherein:

said step of employing said optical element for transmitting said optical beams therethrough is a step of employing said optical element with at least two portions of different diffraction indexes for transmitting said beams through.

Rule 1.12  
Sub  
A2  
end

09/05/06 - 10:10:00

5

10

15

20

25

30

35